

# KSV

THE ALL-PURPOSE MACHINE. THE KSV.



The Schechtl KSV is the reinforced version of the KS and also available with a working length of 2540 mm. The clamping beam consists of rolled profiles, the lower and bending beam of a steel construction. The comprehensive optional accessories and wide range of applications make the KSV the ultimate machine for the sheet metalworking trade.

## BENEFITS

- ✓ **Virtually indestructible** – lasts for generations
- ✓ Realises **unusual profiles**
- ✓ **High working convenience** – back-friendly working height
- ✓ **Maintenance-free** bearings and guides
- ✓ **Versatile** through a comprehensive range of accessories

## TECHNICAL DATA

Subject to change

MODEL	KSV		200	250
<b>WORKING LENGTH</b>		mm	2040	2540
<b>OUTPUT</b>	Steel (400N/mm <sup>2</sup> )	mm	1,50	1,00
	Stainless steel (600N/mm <sup>2</sup> )	mm	0,90	0,60
	Cooper (300N/mm <sup>2</sup> )	mm	1,50	1,25
	Aluminium (250N/mm <sup>2</sup> )	mm	2,00	1,50
	Zinc (150N/mm <sup>2</sup> )	mm	3,00	2,50
<b>DIMENSIONS</b>	Length	mm	2675	3175
	Depth	mm	667	667
	Overall height	mm	1302	1302
<b>WEIGHT</b>		kg	870	1090
<b>CLAMPING BEAMS</b>	Opening height	mm	80	80

# SERIES EQUIPMENT

The following series equipment is possible depending on the version (working length/control):

- ✓ Sharp rail 20° R 1 mm offset
- ✓ Insert rail 10 mm
- ✓ Insert rail 24 mm
- ✓ Foot pedal

---

## ADD-ONS - OPTIMISE YOUR KSV

The following add-ons are possible depending on the version (working length/control):

- ✓ Roller shear
- ✓ Manual back gauge 750 mm
- ✓ Beading apparatus
- ✓ Advice on rails

---

All details onKSV