

MAX

FAST AND VERSATILE. THE MAX.



The Schechtl MAX is perfect where there is extensive work to be done on roofs and exteriors. With a range of control systems and backgauge options as well as a wide selection of rails, the MAX can be fully customised to suit your wishes.

BENEFITS

- ✓ Ideal for high workloads
- ✓ Short bending times through extremely high swivel speed
- ✓ Time-saving through **1-man operation**
- ✓ **Minimal maintenance effort**
- ✓ **Versatile** through a comprehensive range of accessories

TECHNICAL DATA

Subject to change

MODEL	MAX		400	310	250
WORKING LENGTH		mm	4040	3100	2540
OUTPUT	Steel (400N/mm ²)	mm	1,00	1,50	2,00
	Stainless steel (600N/mm ²)	mm	0,60	1,00	1,25
	Cooper (300N/mm ²)	mm	1,00	2,00	2,50
	Aluminium (250N/mm ²)	mm	1,50	2,00	3,00
	Zinc (150N/mm ²)	mm	2,00	3,00	3,50
DIMENSIONS	Length	mm	5147	4207	3647
	Depth	mm	1842	1842	1842
	Overall height	mm	1745	1745	1745
WEIGHT		kg	3600	3100	2800
CLAMPING BEAMS	Opening height	mm	140	140	140

CONTROLS

TheMAXis available with the following controls.

- ✓ ST
 - ✓ CNC S-Touch
 - ✓ ECT
-

SERIES EQUIPMENT

The following series equipment is possible depending on the version (working length/control):

- ✓ Sharp rail 20° R 1 mm offset
 - ✓ Insert rail 10 mm
 - ✓ Insert rail 24 mm
 - ✓ Motorized backgauge 6-750 mm
 - ✓ Motorized backgauge 6-1000 mm
 - ✓ Foot switch
 - ✓ two foot switches
-

ADD-ONS - OPTIMISE YOUR MAX

The following add-ons are possible depending on the version (working length/control):

- ✓ Roller shear RSL
 - ✓ Manual back gauge 750 mm
 - ✓ Conical backgauge fingers
 - ✓ PC offline software
 - ✓ Advice on rails
 - ✓ Advice on backgauges
-

All details onMAX